

Data Sheet

Model: BSF12/22

General Purpose Chamber Furnace



INTRODUCTION

The **BSF12** General Purpose chamber furnace design makes it ideal for treating heavier loads and the processing of material that could contaminate floor mounted heating elements through spillage and it is available in various capacities ranging from 4 liters to 45 liters in standard versions. Other chamber capacities/volumes are offered in custom-built models.

The **BSF12/22** General purpose chamber furnace has a 22-liter capacity.

SPECIFICATIONS

Maximum Temperature: 1200°C

Maximum Continuous Temperature: 1150°C

| Chamber dimensions (mm)- 203 x 228 x 454 (H x W x D)

| Protection of the elements from carbon build-up or corrosive atmosphere, inherent in the slab design of BSF furnaces.

| Vertical lifting door keeps the hot face away from the operator when the door is opened.

| Positive break door safety switch isolates heating elements from power supply when door is open.

| High end Microprocessor PID controller.

| The heating elements are manufactured from high temperature resistance wire spirals embedded in a cast refractory slab, mounted on two sides of the chamber.

| A small ceramic chimney is fitted as standard.

| Replaceable ceramic hearth tile.



BSF12/22

| **External Dimensions (mm):** 780 x 632 x 692 (H x W x D)
(Indicative)

| **Net Wt.:** 137 kg

| **Supply / Power:** 230V– 1 Phase – 5.0 Kw

OPTIONS

| 4 side heating elements is available for when heavier loads, or metal retorts are fitted

| Over temperature protection controller

| Multi segment, multi program storage controllers

Elite Thermal Systems Ltd

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com