



## INTRODUCTION

The **BRF14** high-temperature furnace features a chamber capacity that varies from 5 to 27 liters in its standard configurations. Additional chamber sizes and volumes are available in customized models.

The **BRF14/10** high-temperature furnace has a capacity of 10 liters.

## SPECIFICATIONS

**Maximum Temperature:** 1400°C

**Maximum Continuous Temperature:** 1350°C

**Chamber dimensions (mm):** 190 x 180 x 305 (H x W x D)

Silicon carbide rod heating elements offer an extended operational lifespan and withstand the stress of intermittent operation

Energy efficient, high quality, low thermal mass ceramic fiber insulation

A manually operated, insulated vertical lift door opens upward and outward, keeping the hot face away from the operator

To ensure maximum operator safety, a positive break door switch isolates power from the heating elements whenever the door is opened

High end Microprocessor PID controller

R type Thermocouple

A small ceramic chimney is fitted as standard



## BRF14/10

**External Dimensions (mm):** 780 x 635 x 715 (H x W x D)  
(Indicative)

**Net Wt.:** 74 kg

**Power Supply:** 230V– 1 Phase

**Energy rating:** 7.5 kW (Nominal)  
10.5 kW (Peak power)

## OPTIONS

Electrically operated door

Multi segment, multi program storage Controller

Digital over-temperature protection

## Elite Thermal Systems Limited

Units F1-F2 and F3, Welland Business Park, Valley Way, Market Harborough. Leicestershire. LE16 7PS, UK

Tel: +44 (0)1858 469834 | E-mail: [contact@elitefurnaces.com](mailto:contact@elitefurnaces.com) | Website: [www.elitefurnaces.com](http://www.elitefurnaces.com)