Data Sheet Model: BAF500/30-SS-F-DIG 500°C High temperature ovens



INTRODUCTION

The **BAF500** is a front-loading high-temperature air recirculating oven, manufactured to the highest specification, having high-efficiency insulation in the doors and walls. Heavy-duty hinges, catches, and high-temperature seals are standard.

The BAF500 range offers a choice of chamber capacities ranging from 30 to 120 liters. **BAF500/30-SS-F-DIG** has a 30-litre capacity chamber.



SPECIFICATIONS

Standard Temperature range: 40 °C to 500 °C

Internal Chamber (mm): H x W x D 250 x 250 x 500

No. of Self positions: 2

No. of Shelves supplied: 2

Shelf size (WXD)mm: 250 x 500 (Indicatively)

- The air is heated by Incoloy sheathed tubular elements that are fitted within ducts on each side of the chamber.
- Air drawn into the fan recirculation system from the rear of the oven chamber, passes over the heating elements, thereby pre-heating the air before it enters the chamber. The pre-heated air is then drawn in from the front of the oven chamber and over the samples.
- Constructed from sheet steel finished in easy clean stove powder paint. The door and chamber are fitted with high temperature seals.

A small portion of the recirculating air is vented from the top of the chamber allowing any fumes to be directed into the customers extraction facility.

BAF500/30-SS-F-DIG

External Dimensions (mm):	Н	х	W	х	D	Net Wt.
(Nominal)	777	'x	635	Х	1020	80 kg

Maximum load height (mm): 200

Supply / Power: 230V- 1 Phase - 3000 Watts.

OPTIONAL FEATURES

Independent Overtemperature Protection System.

- Additional vents can be factory fitted if required.
- Extra Shelves can be supplied.
- Multi segment, multi program storage controller.
- Calibration certificates, if required.
- Other options are also available, please contact us.

Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com