

# Data Sheet

Model: BMF11/7-VRP

Laboratory Ashing Furnace



## INTRODUCTION

The **BMF11-VRP** Laboratory Ashing furnace offers a choice of chamber capacities ranging from 3 & 7 litres in standard versions. Other chamber capacities/volumes are offered in custom-built models.

The **BMF11/7-VRP** Laboratory Ashing furnace has a 7-liter capacity.

## SPECIFICATIONS

**Maximum Temperature:** 1100°C

**Maximum Continuous Temperature:** 1050°C

| Chamber dimensions (mm)- 130 x 180 x 310 (H x W x D)

| Wire wound muffle.

| Compact bench mounted design.

| Designed for Ashing applications.

| Energy efficient, high quality, low thermal mass insulation.

| The BMF model provides a pre-heated airflow system and a large metal chimney to ensure good combustion conditions within the chamber and improved process fume removal from the chamber.

| Insulated door opens upwards and outwards keeping the hot face away from the operator.

| ELITE PID controller offering 8 programs with 8 segments each.

| Hard ceramic base is fitted as standard.



**BMF11/7-VRP**

| **External Dimensions (mm):** 675 x 532 x 520 (H x W x D)  
(Indicative)

| **Net Wt.:** 39 kg

| Supply / Power: 230V– 1 Phase – 3.0 Kw

## OPTIONS

| Independent Over-temperature protection system

| Multi segment, multi program storage controllers

| Powered exhaust, Chimney with fan

| Crucibles (Alumina/Fused Silica)

| Lids (Required while cooling)

| Sample Trays

| Tray Loading Handles

## Elite Thermal Systems Ltd

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK

Tel: +44 (0)1858 469834 | E-mail: [contact@elitefurnaces.com](mailto:contact@elitefurnaces.com) | Website: [www.elitefurnaces.com](http://www.elitefurnaces.com)