# Data Sheet Model: BSF12/15A

Laboratory Ashing Furnace



#### INTRODUCTION

The **BSF12/A** Laboratory Ashing furnace design makes it ideal for treating heavier loads and for processing of material that could contaminate floor mounted heating elements through spillage. it is available in various capacities ranging from 4 liters to 45 liters in standard versions. Other chamber capacities/volumes are offered in custom-built models.

BSF12/15A has a 15-liter capacity.

#### SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

Chamber (mm) - H x W x D 220 x 220 x 310

An ashing feature which provides optimum combustion conditions within the chamber, and improved process fume removal from the chamber.

Ideal for ashing foods, plastics, coal & other hydrocarbon materials.

Protection of the elements from carbon buildup or corrosive atmosphere, inherent in the slab design of BSF furnaces.

Vertical lifting door keeps the hot face away from the operator when the door is opened.

Positive break door safety switch isolates heating elements from power supply when door is opened.

High-end micro-processor PID controller.

The heating elements are manufactured from high temperature resistance wire spirals embedded in a cast refractory slab, mounted on two sides of the chamber.

A large metal chimney and hard ceramic base are fitted as standard.



BSF12/15A

| External Dimensions (mm): H x W x D Net Wt. (Indicative only) 727 x 582 x 645 75 kg

Supply / Power: 230V- 1 Phase - 3000 Watts

### OPTIONAL FEATURES

- 4 Side heating elements are available for all round heating when heavier loads, or metal retorts are fitted.
- Over temperature protection controller.
- Multi segment, multi program storage controllers.

## **Elite Thermal Systems Limited**