

Data Sheet

Model: BIF15/102

Light Industrial Chamber Furnace



INTRODUCTION

The **BIF** furnaces are designed for high temperature heat treatment applications for high temperature materials such as precious metals & technical ceramics. BIF15 offers chamber capacity ranging from 102 to 203 liters in standard versions. Other chamber capacities/volumes are offered in custom-built models.

BIF15/102 chamber furnace has a 102-liter capacity.

SPECIFICATIONS

Maximum Temperature: 1500°C

Maximum Continuous Temperature: 1500°C

Chamber (mm) - H x W x D
350 x 450 x 650

The above dimensions are indicative

- | Vertically mounted silicon carbide rods.
- | Generally low thermal mass insulation with brick front and hearth.
- | The furnace is fitted with an electrically operated upward opening door on a parallel link that keeps the hot face away from the operator.
- | Independent Overtemperature protection system.
- | R-type thermocouple.
- | High end Microprocessor/programmable controller.
- | Door switch isolates power from the heating elements whenever the door is opened for maximum safety.
- | A small ceramic chimney is fitted as standard.



BIF15/102

External Dimensions (mm): H x W x D
(Indicatively) 1800 x 950 x 1150

Supply / Power: 400V– 3 Phase – 30000 (approx.) Watts

OPTIONAL FEATURES

- | Multi segment, multi program storage Controllers.

Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK
Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com