

# Data Sheet

Model: BIF17/227

Light Industrial Chamber Furnace



## INTRODUCTION

The **BIF** furnaces are designed for high temperature heat treatment applications for high temperature materials such as precious metals & technical ceramics. BIF17 offers chamber capacity ranging from 82 to 227 liters in standard versions. Other chamber capacities/volumes are offered in custom-built models.

**BIF17/227** chamber furnace has a 227-liter capacity.

## SPECIFICATIONS

**Maximum Temperature:** 1700°C

**Maximum Continuous Temperature:** 1700°C

| Chamber (mm) - H x W x D  
610 x 610 x 610

**The above dimensions are indicative**

| Substantial Molybdenum Disilicide loop elements mounted on 2 chamber sides.

| Dense refractory front vestibule, chamber floor and part side walls; remainder low thermal mass ceramic fibre materials.

| Robust rolled hollow section steel framework with folded edge infill panels, all finished in a durable stoved epoxy enamel.

| Over temperature protection is included in the standard specification.

| The furnace is fitted with an electrically operated upward opening door on a parallel link that keeps the hot face away from the operator.

| B-type thermocouple.

| High end Microprocessor/programmable controller.

| A small ceramic chimney is fitted as standard.



**BIF17/227**

| **External Dimensions (mm):** H x W x D  
(Indicatively) 2150 x 1610 x 1200

| Supply / Power: 400V– 3 Phase – 36000 (approx.) Watts

## OPTIONAL FEATURES

| Multi segment, multi program storage Controllers.

## Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK  
Tel: +44 (0)1858 469834 | E-mail: [contact@elitefurnaces.com](mailto:contact@elitefurnaces.com) | Website: [www.elitefurnaces.com](http://www.elitefurnaces.com)