Data Sheet Model: TMH12(Z3)/38/500

1200 °C Maximum Temperature, Three Zone Horizontal Tube Furnace



INTRODUCTION

The TMH12(Z3) furnace is a bench mounted tube furnace ideal for most general laboratory thermal processing applications.

The TMH12(Z3)/38 Three Zone Tube furnace has an internal tube diameter of 38 mm. TMH12(Z3)/38/500 comes with a heated zone length of 500 mm.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- The TMH(Z3) furnaces are designed to give a longer uniform centre zone temperature than that of the single zone tube furnace models.
- All TMH(Z3) models are controlled by retransmission of set point from the centre zone controller to the end zone controllers.
- This system provides a longer uniform zone temperature than that achieved by the use of single zone furnace of the same length.
- Protective outer mesh covers for improved operator safety.
- High grade resistance wire elements wound onto a ceramic work tube which is an integral part of the furnace.
- Energy efficient, high quality, low thermal mass insulation.
- Temperature Sensor: 'N' Type Sensor.
- High end Microprocessor PID controller.
- Horizontal models are supplied as standard with controls in the base.



TMH12(Z3)/38/500

External Dimensions (mm): H x W x D **Net Wt.** (Nominal) TMH12(Z3)/38/500 560 x 605 x 315 16 kg

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 1.8 kW

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- I The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controller.
- Over temperature protection controller.

Vertical versions are available at extra cost, which will have separate temperature console

Elite Thermal Systems Limited