Data Sheet Model: TMV12(Z3)/100/940

1200 ^oC Maximum Temperature, Three Zone Vertical Tube Furnace



INTRODUCTION

The TMV12 furnace is a vertical-mounted tube furnace with a separate control console, ideal for most general laboratory thermal processing applications.

The TMV12(Z3)/100 Three Zone Tube furnace has an internal tube diameter of 100 mm. TMV12(Z3)/100/940 comes with a heated zone length of 940 mm.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- The TMV(Z3) furnaces are designed to give a longer uniform centre zone temperature than that of the single zone tube furnace models.
- All TMV(Z3) models are controlled by retransmission of set point from the centre zone controller to the end zone controllers.
- This system provides a longer uniform zone temperature than that achieved by the use of single zone furnace of the same length.
- Protective outer mesh covers for improved operator safety.
- High grade resistance wire elements wound onto a ceramic work tube which is an integral part of the furnace.
- Energy efficient, high quality, low thermal mass insulation.
- Temperature Sensor: 'N' Type Sensor.
- High end Microprocessor PID controller.
- Vertical models are supplied as separate control console remote from furnace, separated by 2 meters of flexible interconnecting cable.



TMV12(Z3)/100/940

- **External Dimensions (mm):** H x W x D **Net Wt.** (Nominal) TMV12(Z3)/100/940
- Supply: 230V- 1 Phase 50/60Hz
- Energy rating: 5.2 kW

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- I The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controller.
- Over temperature protection controller.

Elite Thermal Systems Limited