# Data Sheet Model: TMV15(Z3)/90/610

1500 <sup>o</sup>C Maximum Temperature, Three Zone Vertical Tube Furnace



#### INTRODUCTION

The TMV15 furnace is a vertical-mounted tube furnace with a separate control console, ideal for most general laboratory thermal processing applications.

The TMV15(Z3)/90 Three Zone Tube furnace has an outer tube diameter of 90 mm. TMV15(Z3)/90/610 comes with a heated zone length of 610 mm.

#### SPECIFICATIONS

Maximum Temperature: 1500 °C

Maximum Continuous Temperature: 1500 °C

- The TMV(Z3) furnaces are designed to give a longer uniform centre zone temperature than that of the single zone tube furnace models.
- All TMV models are controlled by retransmission of set point from the centre zone controller to the end zone controllers.
- This system provides a longer uniform zone temperature than that achieved by the use of single zone furnace of the same length.
- Protective outer mesh covers for improved operator safety.
- Top grade silicon carbide rods in all 3 heated zones.
- Energy efficient, high quality, low thermal mass insulation.
- Temperature Sensor: Thermocouple, type "R".
- A work tube is not supplied as an integral part of the furnace and therefore needs to be ordered with the furnace as it is an essential accessory.
- High end Microprocessor PID controller.
- Horizontal models are supplied as standard with controls in the base.



TMV15(Z3)/90/610

**External Dimensions (mm):** H x W x D **Net Wt.** (Nominal) TMV15(Z3)/90/610

Supply: 400V-3 Phase

Energy rating: 7.5 kW (Average) 23.0 kW (Peak)

### OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of end seals for work tubes to allow processing under Vacuum or gas atmospheres.
- Over Temperature protection controller.
- Multi segment, multi program storage controllers.

## **Elite Thermal Systems Limited**