# Data Sheet Model: TSH12/25/250

1200 °C Maximum Temperature, Single Zone Horizontal Tube Furnace



### INTRODUCTION

The TSH12 furnace is a bench mounted tube furnace ideal for most general laboratory thermal processing applications.

The TSH12/25 Single Zone Tube furnace has an internal tube diameter of 25 mm. TSH12/25 range offers a choice of two heated zone lengths of 250 mm & 500 mm.

TSH12/25/250 comes with a heated zone length of 250 mm.

#### **SPECIFICATIONS**

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- The furnace design incorporates an integral elemental tube.
- Protective outer mesh covers for improved operator safety.
- High grade resistance wire wound heating elements.
- Energy efficient, high quality, low thermal mass insulation.
- For aggressive processes, a separate work tube is recommended to minimise the risk of contaminating the elemental work tube.
- A rugged metal sheathed control thermocouple is protected from accidental damage and allows full use of work tube bore.
- Temperature Sensor: 'N' Type thermocouple.
- High end Microprocessor PID controller.
- Horizontal models are supplied as standard with controls in the base.



TSH12/25/250

| External Dimensions (mm): H x W x D | Net Wt. (Nominal) TSH12/25/250 | 560 x 335 x 315 | 11 kg

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 0.8 kW.

#### OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controller.
- Over temperature protection controller.

Vertical versions are available which have a separate console

## **Elite Thermal Systems Limited**