Data Sheet Model: TSH14/50/450

1400 °C Maximum Temperature, Single Zone Horizontal Tube Furnace



INTRODUCTION

The TSH14 furnace is a bench mounted tube furnace ideal for most general laboratory thermal processing applications.

The TSH14/50 Single Zone Tube furnace can accept a work tube with internal tube diameter of 50 mm. TSH14/50 range offers a choice of three heated zone lengths of 180 mm, 450 mm & 610 mm.

TSH14/50/450 comes with a heated zone length of 450 mm.



TSH14/50/450

SPECIFICATIONS

Maximum Temperature: 1400 °C

Maximum Continuous Temperature: 1350 °C

- These models are heated by axially mounted silicon carbide elements around the work tube for fast heat up and excellent temperature uniformity.
- This furnace design requires the use of a separate work tube of a grade suitable for the maximum temperature rating of 1400 °C.
- A work tube is not supplied as an integral part of the furnace and therefore needs to be purchased with the order as it is an essential accessory.
- Temperature Sensor: 'R' type Thermocouple.
- Energy efficient, high quality, low thermal mass insulation.
- High end Microprocessor PID controller.
- Horizontal models are supplied as standard with controls in the base.

| External Dimensions (mm): H x W x D Net Wt. (Nominal) TSH14/50/450 715 x 1000 x 460 70 kg

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 4.5 kW (Average) 5.8 kW (Peak)

OPTIONS

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controllers.
- Over temperature protection controller.
- Thermal Radiation Plugs.

Vertical versions are available which have a separate console

Elite Thermal Systems Limited