Data Sheet Model: TSH16/75/450

1600 °C Maximum Temperature, Single Zone Horizontal Tube Furnace



INTRODUCTION

The TSH16 furnace is a bench mounted tube furnace ideal for most general laboratory thermal processing applications.

The TSH16/75 Single Zone Tube furnace can accept a work tube with internal tube diameter of 75 mm. TSH16/75 range offers a choice of two heated zone lengths of 450 mm & 610 mm.

TSH16/75/450 comes with a heated zone length of 450 mm.



TSH16/75/450

SPECIFICATIONS

Maximum Temperature: 1600°C

Maximum Continuous Temperature: 1600 °C

- These models are heated by axially mounted silicon carbide elements around the work tube for fast heat up and excellent temperature uniformity.
- This furnace design requires the use of a separate work tube of a grade suitable for the maximum temperature rating of 1600 °C.
- A work tube is not supplied as an integral part of the furnace and therefore needs to be ordered with the furnace as it is an essential accessory.
- Temperature Sensor: 'R' type Thermocouple.
- Energy efficient, high quality, low thermal mass insulation.
- High end Microprocessor PID controller.
- Horizontal models are supplied as standard with controls in the base.

| External Dimensions (mm): H x W x D Net Wt. (Nominal) TSH16/75/450 715 x 1000 x 460 70 kg

Supply: 400V-3 Phase - 50/60Hz

Energy rating: 5.0 kW (Average)

33.0 kW (Peak)

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controllers.
- Over temperature protection controller.
- Thermal Radiation Plugs.

Vertical versions are available which have a separate console

Elite Thermal Systems Limited