

Data Sheet

Model: TSV12/38/500

1200 °C Maximum Temperature,
Single Zone Vertical Tube Furnace



INTRODUCTION

The TSV12 furnace is a vertical-mounted tube furnace with a separate control console, ideal for most general laboratory thermal processing applications.

The TSV12/38 Single Zone Tube furnace has an internal tube diameter of 38 mm. TSV12/38 range offers a choice of two heated zone lengths of 250 mm & 500 mm.

TSV12/38/500 comes with a heated zone length of 500 mm.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- | The furnace design incorporates an integral elemental tube.
- | Protective outer mesh covers for improved operator safety.
- | High grade resistance wire wound heating elements.
- | Energy efficient, high quality, low thermal mass insulation.
- | For aggressive processes, a separate work tube is recommended to minimise the risk of contaminating the elemental work tube.
- | A rugged metal sheathed control thermocouple is protected from accidental damage and allows full use of work tube bore.
- | Temperature Sensor: 'N' Type thermocouple.
- | High end Microprocessor PID controller.
- | Vertical models are supplied as separate control console.



TSV12/38/500

External Dimensions (mm): H x W x D **Net Wt.**
(Nominal) TSV12/38/500

| Supply: 230V– 1 Phase – 50/60Hz

| Energy rating: 1.7 kW.

OPTIONAL FEATURES

- | Work tubes of various materials, lengths and diameters for use in the furnace.
- | The work tubes are available for containment of atmosphere or protection against process contaminants.
- | A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- | Multi segment, multi program storage controller.
- | Over temperature protection controller.

Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK
Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com