Data Sheet Model: TSV12/75/610

1200 °C Maximum Temperature, Single Zone Vertcial Tube Furnace



INTRODUCTION

The TSV12 furnace is a vertical-mounted tube furnace with a separate control console, ideal for most general laboratory thermal processing applications.

The TSV12/75 Single Zone Tube furnace has an internal tube diameter of 75mm. TSV12/75 range offers a choice of two heated zone lengths of 610 mm & 750 mm.

TSV12/75/610 comes with a heated zone length of 610 mm.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

- The furnace design incorporates an integral elemental tube.
- Protective outer mesh covers for improved operator safety.
- High grade resistance wire wound heating elements.
- Energy efficient, high quality, low thermal mass insulation.
- For aggressive processes, a separate work tube is recommended to minimise the risk of contaminating the elemental work tube.
- A rugged metal sheathed control thermocouple is protected from accidental damage and allows full use of work tube bore.
- Temperature Sensor: 'N' Type thermocouple.
- High end Microprocessor PID controller.
- Vertical models are supplied as separate control console.



TSV12/75/610

| External Dimensions (mm): H x W x D Net Wt. (Nominal) TSV12/75/610

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 2.8 kW.

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controller.
- Over temperature protection controller.

Elite Thermal Systems Limited