Data Sheet Model: TSV14/50/610

1400 °C Maximum Temperature, Single Zone Vertical Tube Furnace



INTRODUCTION

The TSV14 furnace is a vertical-mounted tube furnace with a separate control console, ideal for most general laboratory thermal processing applications.

The TSV14/50 Single Zone Tube furnace can accept a work tube with internal tube diameter of 50 mm. TSV14/50 range offers a choice of three heated zone lengths of 180 mm, 450 mm & 610 mm.

TSV14/50/610 comes with a heated zone length of 610 mm.



Maximum Temperature: 1400 °C

Maximum Continuous Temperature: 1400 °C

- These models are heated by silicon carbide rods arranged equally around and parallel with the work tube for fast heat up and excellent temperature uniformity.
- This furnace design requires the use of a separate work tube of a grade suitable for the maximum temperature rating of 1400 °C.
- A work tube is not supplied as an integral part of the furnace and therefore needs to be purchased with the order as it is an essential accessory.
- Temperature Sensor: 'R' type Thermocouple.
- Energy efficient, high quality, low thermal mass insulation.
- High end Microprocessor PID controller.
- Vertical models are supplied as separate control console remote from furnace, separated by 2 meters of flexible interconnecting cable.



TSV14/50/610

- External Dimensions (mm): H x W x D Net Wt. (Nominal) TSV14/50/610
- Supply: 230V- 1 Phase 50/60Hz
- Energy rating: 6.0 kW (Average) 10.1 kW (Peak)

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under vacuum or gas atmospheres.
- Multi segment, multi program storage controllers.
- Over temperature protection controller.
- Thermal Radiation Plugs.

Elite Thermal Systems Limited