# Data Sheet Model: TSV175/50/200

1750 ℃ Maximum Temperature, Single Zone Vertical Tube Furnace



#### INTRODUCTION

The TSV175 furnace is a vertical tube furnace with a separate control panel for most common laboratory thermal processing applications.

The TSV175/50 Single Zone Tube furnace can accept a work tube with internal tube diameter of 50 mm.

TSV175/50/200 comes with a heated zone length of 200mm.

#### SPECIFICATIONS

Maximum Temperature: 1750 °C

Maximum Continuous Temperature: 1750 °C

- These models are heated by lanthanum chromite elements suspended parallel to the work tube.
- This furnace design requires the use of a separate work tube of a grade suitable for the maximum temperature rating of 1750 °C.
- A work tube is not supplied as an integral part of the furnace and therefore needs to be ordered with the furnace as it is an essential accessory.
- Temperature Sensor: 'B' Type Thermocouple.
- Energy efficient, high quality, low thermal mass insulation.
- High end Microprocessor PID controller.
- Over temperature protection controller.
- Vertical models are supplied as separate control console remote from furnace, separated by 2 meters of flexible interconnecting cable.

## TSV175/50/200

| External Dimensions (mm): H x W x D Net Wt. (Nominal) TSV175/75/350 1525 x 940 x 1000 100 kg

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 8.3 kW

### PHASE CONTROL

Phase angle fired thyristor units operating in conjunction with low voltage secondary isolating transformers providing the correct parameters for the heating elements.

### OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace.
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under gas atmospheres.
- Multi segment, multi program storage controllers.
- Thermal Radiation Plugs.

### **Elite Thermal Systems Limited**