Data Sheet Model: TSVH11/90/457

1100 °C Maximum Temperature. Single Zone Vertical Split Tube Furnace



INTRODUCTION

The TSVH is a vertical single zone split tube furnace is designed to meet the needs of 'in-line' thermal processes, and for when rapid cooling is required.

The furnace range offers of choice of three heated zone length, 305mm, 457mm, and 610mm respectively.

TSVH11/90/457 comes with a 90mm furnace bore size, 457mm heated zone length.



TSVH11/90/457

External Dimensions (mm): H x W x D Net Wt. (Nominal) TSVH11/90/457 538 x 557 x 660 46 kg

Supply: 230V- 1 Phase - 50/60Hz

Energy rating: 2.8 kW

OPTIONAL FEATURES

- Work tubes of various materials, lengths and diameters for use in the furnace
- The work tubes are available for containment of atmosphere or protection against process contaminants.
- A variety of triple flange gas tight end seals for work tubes to allow processing under Vacuum or gas atmospheres.
- Multi segment, multi program storage controller
- Over temperature controller.

Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK Tel: +44 (0)1858 469834 E-mail: contact@elitefurnaces.com Website: www.elitefurnaces.com

SPECIFICATIONS

Maximum Temperature: 1100 °C Maximum Continuous Temperature: 1050 °C

This TSVH furnace can be supplied with separate control console on two meters of interconnecting cables.

Heating is by free radiating high-grade resistance wire elements supported on ceramic tubes.

- Energy efficient, high quality, low thermal mass insulation provides fast heating and cooling.
- A work tube is not supplied as an integral part of the furnace and therefore needs to be ordered with the furnace as it is an essential accessory.
- The furnace accepts a range of work tubes up to 90mm outside diameter when used with tube reducer inserts.
- Temperature Sensor: 'N' Type thermocouple.

High end Microprocessor PID controller.