

Data Sheet

Model: TSVH12/90/610

1200 °C Maximum Temperature,
Single Zone Vertical Split Tube Furnace



INTRODUCTION

The TSVH12 is a vertical single zone split tube furnace designed to meet the needs of 'in-line' thermal processes, and for when rapid cooling is required.

The furnace range offers a choice of four heated zone lengths, 305mm, 457mm, 610mm and 940mm respectively.

TSVH12/90/610 comes with a 90mm furnace bore size, 610mm heated zone length.

SPECIFICATIONS

Maximum Temperature: 1200 °C

Maximum Continuous Temperature: 1150 °C

| This TSVH furnace can be supplied with separate control console on two meters of interconnecting cables.

| Heating is by free radiating high-grade resistance wire elements supported on ceramic tubes.

| Energy efficient, high quality, low thermal mass insulation provides fast heating and cooling.

| A work tube is not supplied as an integral part of the furnace and therefore needs to be ordered with the furnace as it is an essential accessory.

| The furnace accepts a range of work tubes up to 90mm outside diameter when used with tube reducer inserts.

| Temperature Sensor: 'N' Type thermocouple.

| High end Microprocessor PID controller.



TSVH12/90/610

| **External Dimensions (mm):** H x W x D **Net Wt.**
(Nominal) TSVH12/90/610 538 x 710 x 660 72 kg

| Supply: 230V– 1 Phase – 50/60Hz

| Energy rating: 5.0 kW

OPTIONAL FEATURES

| Work tubes of various materials, lengths and diameters for use in the furnace.

| The work tubes are available for containment of atmosphere or protection against process contaminants.

| A variety of triple flange gas tight end seals for work tubes to allow processing under Vacuum or gas atmospheres.

| Multi segment, multi program storage controller.

| Over temperature controller.

Elite Thermal Systems Limited

Elite Court, 6 Stuart Road, Market Harborough, Leicestershire LE16 9PQ, UK

Tel: +44 (0)1858 469834 | E-mail: contact@elitefurnaces.com | Website: www.elitefurnaces.com